

**TENTH INTERNATIONAL CONFERENCE ON
SUPERPLASTICIZERS AND OTHER CHEMICAL
ADMIXTURES IN CONCRETE**



**SCC and HPC (70 MPa) for a
Massive Block Foundation**



"do Laboratório de Pesquisa ao Canteiro de Obras"

**Carlos Britez
Juan Gadea
Paulo Helene**
*PhD Engenharia
IBRACON
Universidade de São Paulo*

International Conferences October 29, 2012 Prague, Czech Republic

1

**TENTH INTERNATIONAL CONFERENCE ON
SUPERPLASTICIZERS AND OTHER CHEMICAL
ADMIXTURES IN CONCRETE**



SCC and HPC (70 MPa) for a Massive Block Foundation
***...from university lab
research to job site...***



"do Laboratório de Pesquisa ao Canteiro de Obras"

**Carlos Britez
Juan Gadea
Paulo Helene**
*PhD Engenharia
IBRACON
Universidade de São Paulo*

International Conferences October 29, 2012 Prague, Czech Republic

2



**70 MPa
(10,000psi)
(84,000ft³)
2,378m³**


3



**70 MPa
(10,000psi)
(84,000ft³)
2,378m³**

**28.40m x 18.60m x 4.5m
93ft x 61ft x 14.7ft**

4



5

Cement & Admixture

- 0,5% → SIKAMENT 735 plasticizer admixture
- 1% → SIKAMENT 5700 superplasticizer admixture
- ABNT NBR 11768 (S & SP)
- ASTM 494 (A & F)
- PCE modified

- compatibility tests
- blast furnace cement {60% + 40% (clinker + gypsum)}

PhD Engenharia

6



World Business Council for Sustainable Development

Cement Sustainability Initiative

WBCSD → CSI, said in the “Getting the Numbers Right”, 2010:

1. ...“Brazil is the leader in the use of biomass as substitute fuel, with 12% of total thermal energy generated...;
2. also ... "cement / clinker = 0.58, one the best relation ship in the world...”

PhD Engenharia

7


Cement & Admixture

- **0,5% → SIKAMENT 735 plasticizer admixture**
- **1% → SIKAMENT 5700 superplasticizer admixture**
- **ABNT NBR 11768 (S & SP)**
- **ASTM 494 (A & F)**
- **PCE modified**

- **compatibility tests**
- **blast furnace cement {60% + 40% (clinker + gypsum)}**
- **8.5% silica fume**
- **W/cementitious = 0.36**

PhD Engenharia

8



9

5 steps procedures

- ✓ **mix design lab tests**
- ✓ **thermal simulations**
- ✓ **concrete production procedures**
- ✓ **concrete casting and control procedures**
- ✓ **technical control at site**

PhD Engenharia

10

5 steps procedures

- ✓ **mix design lab tests**
- ✓ **thermal simulations**
- ✓ **concrete production procedures**
- ✓ **concrete casting and control procedures**
- ✓ **technical control at site**

PhD Engenharia

11

IBRACON Concrete Mix Proportion Method



optimal mortar proportion



12

Mix Design Research

50 days before foundation block casting

lab tests



potentials mix proportions



mixing concrete in trucks




complete field test

PhD Engenharia

13


Control of Materials



14

complete field test

casting parking columns
concrete no ice
slump: SCC
severe test conditions
concrete temperature 37° C
ambient temperature 32° C



PhD Engenharia

15



16


Temperature and Times

Controle de tempo	
beginning in concrete plant	12:55
go out of concrete plant	13:35
arriving at job site	14:30
finishing casting	16:00
job site concrete temperature	
37,5 °C	

PhD Engenharia

17

plasticizer → slump (20 – 40mm)
superplasticizer → flow (600 – 750mm)



18

Density and air entrapped



19




20

flow and t500 → NBR 15823 → Parte 2
ASTM C 1611 & EN 12350-8



21

J Ring → NBR 15823 → Parte 3
ASTM C 1621 & EN 12350-12



22

L Box → NBR 15823 → Parte 4
EN 12350-10



23

V Funnil → NBR 15823 → Parte 5
EN 12350



24

Column segregation → NBR 15823 → Parte 6
ASTM C 1610



25

Hour/Time → Temperature → RU%



26

Mix Proportions per cubic meter

Mix proportions per feet cubic

Cement content	= 447kg	= 27.8 lb
Silica fume	= 38kg	= 2.4 lb
Artificial sand	= 481kg	= 30.0 lb
Natural sand	= 321 kg	= 20.9 lb
Crushed stone 9 – 19mm	= 194 kg	= 12.0 lb
Crushed stone 19 - 25mm	= 777 kg	= 48.4 lb
Total water	= 175 L	= 10.5 lb
Density	= 2,438 kg/m ³	
Density	= 152 lb / ft ³	

PhD Engenharia

27

Mix Proportions per cubic meter

Mix proportions per feet cubic

OPC	= 180kg	= 11.0 lb
Blast furnace	= 268kg	= 16.7lb
Silica fume	= 38kg	= 2.4 lb
Artificial sand	= 481kg	= 30.0 lb
Natural sand	= 321 kg	= 20.9 lb
Crushed stone 9 – 19mm	= 194 kg	= 12.0 lb
Crushed stone 19 - 25mm	= 777 kg	= 48.4 lb
Total water	= 175 L	= 10.5 lb
Density	= 2,438 kg/m ³	
Density	= 152 lb / ft ³	

PhD Engenharia

28

5 steps procedures

- ✓ mix design lab tests
- ✓ **thermal simulations**
- ✓ concrete production procedures
- ✓ concrete casting and control procedures
- ✓ technical control at site

PhD Engenharia

29

Ice thermal calculations

Material	Consumo kg/m ³	Calor específico kcal/kg.°C	q=m.c (kcal/m ³ .°C)	T (°C)	Q (kcal/m ³)
Cimento.CPIII-40	447,0	0,222	99,2	70	6946,3
Silica	38,3	0,191	7,3	40	292,6
Areia Artificial	480,9	0,175	84,1	23	1935,6
Areia Natural	320,6	0,181	58,0	26	1508,7
Brita 0	194,2	0,175	33,9	26	883,6
Brita 1	776,8	0,175	135,9	26	3534,4
Água	134,9	1,000	134,9	26	3508,0
Umidade Miúdo Ar.	24,0	1,000	24,0	26	625,1
Umidade Miúdo Nat.	16,0	1,000	16,0	26	416,7
Umidade Graúdo	0	1,000	0	26	0
Betoneira					1000
Total			593,6604		20651,4
Transporte (Ganho)		2,0°C			
T Lançamento=		36,8°C			

without ice

PhD Engenharia

30

Ice thermal calculations


Material	Consumo kg/m ³	Calor específico kcal/kg.°C	q=m.c (kcal/m ³ .°C)	Ti (°C)	Tf (°C)	Ti - Tf (°C)	Q (kcal/m ³)
Cimento.CPIII-40	447,0	0,222	99,2	70	0	70	6946,3
Sílica	38,3	0,191	7,3	40	0	40	292,6
Areia Artificial	480,9	0,175	84,1	23	0	23	1935,6
Areia Natural	320,6	0,181	58,0	26	0	26	1508,7
Brita 0	194,2	0,175	33,9	26	0	26	883,6
Brita 1	776,8	0,175	135,9	26	0	26	3534,4
Água	0	1,000	0	26	0	26	0
Umidade Miúdo Art.	24,0	1,000	24,0	26	0	26	625,1
Umidade Miúdo Nat.	16,0	1,000	16,0	26	0	26	416,7
Umidade Graúdo	0	1,000	0	26	0	26	0
Gelo	134,9	0,500	67,4	-10	0	-10	-674,6
Fusão Gelo	134,9	1,000	134,9	0	0	0	-10794,0
Gelo + Água	134,9	1,000	134,9	0	18	-18	-2428,6
Betoneira							1000
Total			796,0				3246,0
Transporte (Ganho)		2,0°C					
T Lançamento=		6,1°C					

with ice

PhD Engenharia

31


Thermal simulations for 2 layers



PhD Engenharia

32


3 days → temperatures



PhD Engenharia

33


Thermal curves



PhD Engenharia

34


tensions



PhD Engenharia

35


Thermal simulations 4 layers



PhD Engenharia

36


Thermal curves, 4 layers each 3days



PhD Engenharia

37

tensions



PhD Engenharia

38

5 steps procedures

- ✓ **mix design lab tests**
- ✓ **thermal simulations**
- ✓ **concrete production procedures**
- ✓ **concrete casting and control procedures**
- ✓ **technical control at site**

PhD Engenharia

39

Procedures

Concrete Production at Concrete Plant :

- Medir temperatura agregados e cimento
- Molhar agregado graúdo (refrigeração)
- Substituição de toda a água de amassamento por gelo
- Pesagem dos sacos de gelo para determinar peso médio
- Medir umidade da areia
- Carregar apenas 6m³ por CB, já com aditivo
- Fluxo constante de caminhões betoneira

Acceptance Control at job site :

- Medir temperatura do concreto
- Medir consistência
- Moldar corpos de prova (compressão e módulo)
- Medir temperatura do concreto da viga com termopares

Casting procedures :

- Posicionamento bombas
- Precaução contra chuva
- Cálculo das formas
- Cura

PhD Engenharia

40

Concrete production at Concrete Plant



Wetting aggregates

PhD Engenharia

43

concrete production at concrete plant ice in cubes



Direitos Reservados 2009

44 *PhD Engenharia*

44


5 steps procedures

- ✓ **mix design lab tests**
- ✓ **thermal simulations**
- ✓ **concrete production procedures**
- ✓ **concrete casting and control procedures**
- ✓ **technical control at site**

PhD Engenharia

45

concrete temperature



PhD Engenharia

46

concrete flow



Direitos Reservados 2009

47 **PhD Engenharia**

47

Temperature control inside concrete thermal couples



PhD Engenharia

48

plan concrete casting in job site



49

concrete casting in job site




50

Why SCC?



51



52



53

Concrete casting



54




55

5 steps procedures


- ✓ **mix design lab tests**
- ✓ **thermal simulations**
- ✓ **concrete production procedures**
- ✓ **concrete casting and control procedures**
- ✓ **technical control**

PhD Engenharia

56



57



58




59




60

Why SCC?



61




62



PhD Engenharia

63



64



65




66

advances in concrete technology

- it is possible no problems
- admixture evolution must be know
- needs some experimental tests
- needs to control the quality
- needs holistic vision and SCM
- it is a team job and SCM
- must know standards and literature

PhD Engenharia

67



70 MPa
(10,000psi)
(84,000ft³)
2,378m³

*Beginning time at concrete plant
until final casting 3h (SCC)
at 25° C to 33° C
Thanks to chemical industry for so
important and sustainable
contribution (PCE admixtures)*

OPC	= 180kg	= 11.0 lb
Blast furnace	= 268kg	= 16.7lb
Silica fume	= 38kg	= 2.4 lb

w/c+a = 0.36 → SCC

68



thank you!

PhD

do Laboratório de Pesquisa ao Controle de Obras

PhD Engenharia

www.concretophd.com.br

www.phd.eng.br